

## 250W Mixer Amplifier



## TECHNICAL SPECIFICATIONS

### SPECIFICATION

<b>Rated Power</b>	250W
<b>Speaker Outputs</b>	100V or 70V & 4 Ohms - 8 Ohms-16 Ohms
<b>Connector</b>	Mic1 input by Unbalanced Jack Mic2 Balance XLR Socket Line 1-2 inputs by RCA: Line output by RCA
<b>Attenuation</b>	Microphone 1-2, Line 1-2 and Mp3/FM, bass/treble and master
<b>MIC1 - 2 input Sensitivity</b>	5mV
<b>AUX1 &amp; 2 input Sensitivity</b>	350mV
<b>EMC input Sensitivity MIC</b>	350mV
<b>MIC Frequency response</b>	180Hz - 10kHz (+- 3dB)
<b>AUX Frequency response</b>	70Hz -16Hz (+- 3dB)
<b>Noise</b>	< 5mV (4 Ohm load output terminal)
<b>THD</b>	< 1% 1KHz
<b>Protection</b>	Short Circuit, Clip Overload and high Temp protection
<b>Treble adjustment</b>	10dB (+-2)
<b>Bass adjustment</b>	10dB (+ -2)
<b>Rated Power Supply</b>	AC-110-220V
<b>Rated output voltage</b>	250W/4 Ohm, AC220V
<b>Priority</b>	EMC>MIC1>Other
<b>Dimensions</b>	247 x 198 x 66mm
<b>Packaging Size</b>	343 x 302 x 121mm
<b>Net Weight</b>	2.6Kg
<b>Class</b>	D

