

ELX200

DOES MORE. WEIGHS LESS.

All ELX200 models are available in black or white



POWERED

ELX200-10P

ELX200-12P

ELX200-15P

ELX200-12SP

ELX200-18SP

Application	Pole-mounted / monitor	Pole-mounted / monitor	Pole-mounted / monitor	Subwoofer	Subwoofer
HF transducer	DH-1L 1" titanium compression driver	DH-1L 1" titanium compression driver	DH-1L 1" titanium compression driver	-	-
LF transducer	EVS-10M254 mm (10")	EVS-12M300 mm (12")	EVS-15M381 mm (15")	EVS-12L300 mm (12")	EVS-18L457 mm (18")
Power rating (peak)	1200 W	1200 W	1200 W	1200 W	1200 W
SPL max	130 dB	130 dB	132 dB	129 dB	132 dB
Coverage (H x V)	90° x 60°	90° x 60°	90° x 60°	-	-
Frequency range (-10 dB)	53 Hz-20 kHz	51 Hz-20 kHz	48 Hz-19 kHz	41 Hz-165 Hz	40 Hz-145 Hz
Material	Polypropylene	Polypropylene	Polypropylene	15 mm plywood with EVCoat	15 mm plywood with EVCoat
Digital signal processing	Quickstart DSP features best-in-class processing. Easy setup via four presets, sub/top system-match, three-band EQ, five user-programmable presets, visual monitoring of limiter status, input level control and meters, and master volume control to optimize gain structure, all via LCD.				
Remote control and monitoring	EV Quick Smart Mobile application: quickly and wirelessly configure, control and monitor up to six ELX200 loudspeakers simultaneously and receive immediate notification during critical performance conditions.				
Crossover frequency	1800 Hz	1700 Hz	1600 Hz	-	-
Low-pass frequency	-	-	-	Electro-Voice full range speakers, 80/100/120/150 Hz	Electro-Voice full range speakers, 80/100/120/150 Hz
Connections	1x Stereo RCA input 2x XLR/TRS combo jack 1x XLR link output	1x stereo RCA input 2x XLR/TRS combo jack 1x XLR link output	1x stereo RCA input 2x XLR/TRS combo jack 1x XLR link output	2x XLR RTRS combo jack 2x XLR link output	2x XLR RTRS S combo jack 2x XLR link output
Suspension	(3) M10 suspension points	(3) M10 suspension points	(3) M10 suspension points	-	-
Weight	13.5 kg (29.8 lbs)	15.6 kg (34.4 lbs)	18.9 kg (41.7 lbs)	19.1 kg (42.2 lbs)	28.0 kg (64 lbs)
Dimensions (W x H x D)	330 mm x 531 mm x 319 mm (13.0" x 21.0" x 12.6")	363 mm x 629 mm x 344 mm (14.3" x 24.8" x 13.6")	423 mm x 710 mm x 384 mm (16.7" x 28.0" x 15.2")	445 mm x 397 mm x 457 mm (17.6" x 16.7" x 18.0")	507 mm x 600 mm x 574 mm (20.0" x 23.7" x 22.6")
Colors	Black or white	Black or white	Black or white	Black or white	Black or white
Accessories	ELX200-10-CVR padded cover ELX200-BRKT wall-mount bracket EBK1-M10-3PACK forged M10 3 pack short shank eyebolt kit	ELX200-12-CVR padded cover ELX200-BRKT wall-mount bracket EBK1-M10-3PACK forged M10 3 pack short shank eyebolt kit	ELX200-15-CVR padded cover ELX200-BRKT wall-mount bracket EBK1-M10-3PACK forged M10 3 pack short shank eyebolt kit	ELX200-12S-CVR padded cover ASP-58 adjustable sub pole M20	ELX200-18S-CVR padded cover ASP-58 adjustable sub pole M20

ELX200

DOES MORE. WEIGHS LESS.

All ELX200 models are available in black or white



PASSIVE

ELX200-10

ELX200-12

ELX200-15

ELX200-12S

ELX200-18S

Application	Pole-mounted / monitor	Pole-mounted / monitor	Pole-mounted / monitor	Subwoofer	Subwoofer
HF transducer	DH-1L 1" titanium compression driver	DH-1L 1" titanium compression driver	DH-1L 1" titanium compression driver	-	-
LF transducer	EVS-10M254 mm (10")	EVS-12M300 mm (12")	EVS-15M381 mm (15")	EVS-12L300 mm (12")	EVS-18L457 mm (18")
Powerhandling	300 W continuous, 1200 W peak	300 W continuous, 1200 W peak	300 W continuous, 1200 W peak	400 W continuous, 1600 W peak	400 W continuous, 1600 W peak
SPL max	127 dB	128 dB	130 dB	128 dB	133 dB
Coverage (H x V)	90° x 60°	90° x 60°	90° x 60°	-	-
Frequency range (-10 dB)	49 Hz-22 kHz	40 Hz-22 kHz	51 Hz-20 kHz	33 Hz-300 Hz	28 Hz-300 Hz
Material	Polypropylene	Polypropylene	Polypropylene	15 mm plywood with EVCoat	15 mm plywood with EVCoat
Crossover frequency	2000 Hz	1700 Hz	1600 Hz	-	-
Recommended high-pass frequency	55 Hz	50 Hz	42 Hz	42 Hz	35 Hz
Connectors	Dual NL4	Dual NL4	Dual NL4	Dual NL4	Dual NL4
Suspension	(3) M10 suspension points	(3) M10 suspension points	(3) M10 suspension points	-	-
Weight	13.4 kg (29.6 lbs)	15.2 kg (33.4 lbs)	18.7 kg (41.2 lbs)	122 kg (269 lbs)	26.6 kg (58.7 lbs)
Dimensions (W x H x D)	330 mm x 531 mm x 319 mm (13.0" x 21.0" x 12.6")	363 mm x 629 mm x 344 mm (14.3" x 24.8" x 13.6")	423 mm x 710 mm x 384 mm (16.6" x 28.0" x 15.1")	445 mm x 397 mm x 457 mm (17.6" x 16.7" x 18.0")	507 mm x 600 mm x 574 mm (20.0" x 23.7" x 22.6")
Colors	Black or white	Black or white	Black or white	Black or white	Black or white
Accessories	ELX200-10-CVR padded cover ELX200-BRKT wall-mount bracket EBK1-M10-3PACK forged M10 3 pack short shank eyebolt kit	ELX200-12-CVR padded cover ELX200-BRKT wall-mount bracket EBK1-M10-3PACK forged M10 3 pack short shank eyebolt kit	ELX200-15-CVR padded cover ELX200-BRKT wall-mount bracket EBK1-M10-3PACK forged M10 3 pack short shank eyebolt kit	ELX200-12S-CVR padded cover ASP-58 adjustable sub pole M20	ELX200-18S-CVR padded cover ASP-58 adjustable sub pole M20
Recommended Dynacord amplifier	L1800FD, L2800FD	L1800FD, L2800FD	L1800FD, L2800FD	L2800FD	L2800FD