

## RM-210F AMQ

### REMOTE MICROPHONE EXTENSION



The RM-210F is an expansion unit dedicated for the RM-300X Desk top remote microphone. The number of zone selection keys and indicators of the RM-300X can be increased in 10 units per RM-210F.

### Key features

## Specifications

Power Source	Supplied from the optional RM-300X
Current Consumption	80 mA or less
Audio Output	0 dB(*1), 600 Ω, balanced
External Microphone Input	-40 dB(*1), 2.2 kΩ, unbalanced, ø3.5 mm phone jack (2P) for electret condenser microphone, (phantom power supply:3 V DC)-20 dB(*1), 4.7 kΩ, unbalanced, ø3.5 mm phone jack (2P) (AUX Input)
Distortion	1 % or less
Frequency Response	100 Hz – 20 kHz
Signal to Noise Ratio	60 dB or more
Microphone	Unidirectional electret condenser microphone with AGC (ON/OFF selectable)
Chime	Built inside (PCM sound source), Monitoring possible using built-in speaker
Level Control	Microphone sensitivity control, Monitor speaker volume control, Chime(adjustable using the software)
Number of Function Keys	Function key x 10
Finish	ABS resin, black
Dimensions	110 x 76.5 x 215 mm
Weight	350 g
Optional Accessories	Wall mounting bracket: WB-RM200