



227

12/2 UTP CL3R
 Audio, Control, and Low Voltage Power

Construction & Dimensions

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	2
• AWG Size	12
• Conductor Stranding	19x25
• Conductor Type	Bare copper
• Nominal DCR	1.7 Ohm/1000ft
• Cabling Lay Length	4.5 in
• Twists/Foot	2.7 twist/ft
INSULATION PARAMETER	
• Insulation Type	Th rmoplastic
• Insulation Thi kness	0.012 in
• Insulation Color Code	1. Black 2.White
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	PVC
Jacket Thi kness	0.017 in
Nominal Cable O.D.	0.264 in
Plenum	No
NEC UL Rating	CL3R, FPLR
RoHS Compliant	Yes
Pull Tension	152 lbs
Bend Radius	2.376 in
Cable Weight	61 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	UL1666 Vertical Shaft
Operating Range	-20 to 60 Deg C
UL Voltage Rating	300

Detailed Specification & Technical Data



227

12/2 UTP CL3R

Related Products

RELATED PRODUCTS	
Plenum Number	25227B
Aquaseal Direct Burial Number	AQ227
SpeakOn Panel Mount	CN-NL4MP